

Superstreet Body Rules 2012

ROOF: MUST BE STOCK TYPE ROOF. STEEL OR FIBERGLASS

REAR QUARTER PANELS: CENTER OF AXLE TO REAR OF QUARTER PANEL 50IN MAX

AT REAR OF QUARTER PANEL: 18IN MAX

BEHIND REAR TIRE: 22IN MAX

DOORS: TOP AT DECKING TO BOTTOM OF DOOR 30IN MAX

A-POST- NO SMALLER WIDTH THAN 3 IN.

B-POST- AT TOP OF ROOF LINE 12IN MAX/AT BOTTOM OF DECKING 30 IN MAX

BODY WIDTH- 72 INCHES MAX

NOSE OF CAR: 1. NO DIRT STYLE NOSES, MD3, OR DOMINATOR NOSES

FENDER MUST TIE INTO NOSE. NO FENDER FLAIRS.

52INCH FROM CARBURETOR STUD TO CENTER OF NOSE AT BUMPER. NO OFFSET CARB. STUDS

MUST BE 9INCH FROM GROUND AT BOTTOM OF NOSE AT ANY POINT.

SPOILER: FROM GROUND TO TOP OF SPOILER 41 INCH MAX 5INCH SPOILER WITH 3 BRACES 5"x12"

MUST BE TRACK APPROVED BY WMS!